

Available online at [www.sciencedirect.com](http://www.sciencedirect.com)**ScienceDirect**

Procedia - Social and Behavioral Sciences 195 (2015) 2101 – 2108

**Procedia**  
Social and Behavioral Sciences

World Conference on Technology, Innovation and Entrepreneurship

## Copolymerization of Pyrrole and Thienyl End Capped Cyclohexanone Formaldehyde Resin with Ce(IV) Oxidic Dibenzoate

Yagmur Tatar<sup>a</sup>, Esin Ateş Güvel<sup>b</sup>, Nilgün Kızılcan<sup>b\*</sup><sup>a</sup>Hamburg University of Applied Science, Department of Process Engineering, Hamburg, 21033 Germany<sup>b</sup>Istanbul Technical University, Department of Chemistry, Faculty of Science, Istanbul, 34469 Turkey

### Abstract

Block copolymers of polypyrrole (PPy) and thienyl end capped cyclohexanone formaldehyde resin (ThCFR) were synthesized via chemical oxidative polymerization of (Py) and ThCFR in the presence of cerium (IV) oxidic dibenzoate (CODB). The treatment of Py with CODB was maintained in non-aqueous media at room temperature. Several solvents including toluene, dichloromethane (DCM), were used. Besides the role of reaction media, the effect of ceric (IV) oxidic compound on polymerization was investigated. Reactions with constant amount of Py, and CODB to Py mol ratios of 0.33:1.0, 0.5:1.0 and 1.0:1.0 were observed. The results showed that in one-hour limited time, block copolymers could be obtained in toluene and dichloromethane with CODB: Py: ThCFR mol ratio of 1.0: 1.0: 0.01. Conductivities of polypyrroles were determined by 4-point probe technique. Block copolymers were prepared in dichloromethane and toluene, respectively.

© 2015 The Authors. Published by Elsevier Ltd. This is an open access article under the CC BY-NC-ND license

[\(http://creativecommons.org/licenses/by-nc-nd/4.0/\)](http://creativecommons.org/licenses/by-nc-nd/4.0/).

Peer-review under responsibility of Istanbul University.

**Keywords:** Cerium, conductivity, oxidative polymerization, polypyrrole, ketonic resin

### 1. Introduction

Conductive (or electro-active) polymers are a special type of polymer with extensive  $\pi$ -electron delocalization along their backbones that give rise to interesting optical properties and allows them to become good electrical conductors (typically when oxidized or reduced) (De Leon & Advincula, 2015; Chiang et al., 1977 ). Polypyrrole is an example of heterocyclic conductive polymers (Dall'Olio et al., 1968; De Leon & Advincula, 2015).

\*Corresponding author Tel.: +90-212- 285 32 42; fax: +90-212-285 63 86.

E-mail address: [kizilcan@itu.edu.tr](mailto:kizilcan@itu.edu.tr)

Conductive polypyrrole has received considerable attention because it can be prepared both electrochemically (Diaz et al., 1979; Kızılcın et al., 2001) and by chemical oxidation and because it has relatively good stability in the conducting oxidized form. However, PPy is a hard, brittle, and nonprocessable solid that is insoluble in common solvents (Kızılcın et al., 2001; Gardini, 1973; Sarac et al., 1994).

Still polypyrrole is one of the most investigated conducting polymers, owing to its facile synthesis, good conductivity, redox properties, long-term environmental stability and biocompatibility as polymer in vivo (Hafaid et al., 2010), and has shown promising applications including sensors (Chartuprayoon et al., 2010), actuators (Cho et al., 2008), photovoltaic/solar cells (Guo et al., 2010; Wu et al., 2008), electromagnetic interference shielding (Joo & Lee, 2000), and corrosion protection (Schafinghen et al., 2007). In addition, PPy nanocomposites have been shown biodegradability and biocompatibility, which are potentially useful in drug delivery and tissue engineering (Guimard et al., 2007; Ge et al., 2007; Liao et al., 2012).

Polymerizations initiated by a reaction between an oxidizing and a reducing agent are called redox polymerizations. Redox polymerization has found wide applications in initiating polymerization reactions and has been specifically of industrial importance. The essence of redox initiation is a reduction-oxidation process. In this process an oxidant, i.e., Ce(IV) or Mn(III) forms initially a complex by reacting simply with organic molecules which then decomposes unimolecularly to produce free radicals that initiate polymerization (Öztürk & Cakmak, 2007). There are many reports in the literature on the block copolymer synthesis. Initiation by a redox process is only a method to obtain these types of polymers (Öztürk & Cakmak, 2007; Nagarajan & Srinivason, 1994; Nagarajan & Srinivasan, 1995; Wodka, 1993; Nagarajan et al., 1994). The synthesis of block copolymers by redox systems exerts a number of technical and theoretical advantages over other methods. Because of the applicability at low temperatures, side reactions are minimized (Öztürk & Cakmak, 2007; Cakmak, 1993).

Ceric ions in acidic media are well-known oxidizing agents for various organic substrates (Öztürk & Cakmak, 2007; Trahanovsky et al., 1967). Also, these ions, either by themselves or in combination with reducing agents function as initiators for polymerization (Öztürk & Cakmak, 2007; Leza & Guzman, 1999; Saldick, 1956; Venkatakrishnan & Santappa, 1958; Ananthanarayanan & Santappa, 1965; Mino & Kaizerman, 1958; Misra & Arya, 1984; Fernandez & Guzman, 1989; Sudhakar et al., 1979). A first attempt to initiate polymerization by Ce(IV) in organic solvents was performed in 1979 by Singh et al. (Öztürk & Cakmak, 2007; Singh et al., 1979) who observed that the solvent (toluene) inhibits the redox initiating process for the polymerization of acrylonitrile. The suitable reducing agents reported in the literature are alcohols (Öztürk & Cakmak, 2007; Mino et al., 1959), polyols (Öztürk & Cakmak, 2007; Mohanty et al., 1979), ketones (Öztürk & Cakmak, 2007; Subramanian & Santappa, 1968), acids (Öztürk & Cakmak, 2007; Subramanian & Santappa, M, 1968, amines (Öztürk & Cakmak, 2007; Saha & Chaudhuri, 1972), thiols (Öztürk & Cakmak, 2007; Chakrabarty & Chaudhuri, 1985), and thiourea (Öztürk & Cakmak, 2007; Pramanick et al., 1979).

Most of the commercial resins are generally solid materials with low molecular weight. Also they can be processed easily. These types of resins are mainly used in surface coatings, varnishes, inks, and textile and paper industries as additive materials. Cyclohexanone formaldehyde resin (CFR) is a low molecular weight and shows unique compatibility with a great number of polymers (Kızılcın & Akar, 1996). It is soluble in most organic solvents such as aromatic hydrocarbons, ketones, esters, alcohols, etc. Due to its good compatibility, it is usually used as a coating additive. Copolymers of ketonic resins have been the subject of recent research since the ketonic resin segments improve adhesion, solubility, gloss and light stability of parent polymers. These copolymers have been synthesized via condensation polymerization (Uyanık et al., 1991; Uyanık et al., 1998; Uyanık et al., 2001; Kızılcın & Koşar, 2012), free radical polymerization (Kızılcın, 1999), redox polymerization (Ustamehmetoğlu et al., 2004; Ustamehmetoğlu et al., 2011; Ustamehmetoğlu et al., 2012; Kızılcın & Ustamehmetoğlu, 2005; Kızılcın et al., 2011), promoted cationic polymerisation routes (Ergun et al., 2007) and atom transfer radical polymerization (Çanak et al., 2011 and 2012). The block copolymers of N-vinyl carbazole and  $\alpha,\omega$ -dihydroxy polydimethylsiloxane have been produced in one step at room temperature with the redox initiation system of ceric salt and hydroxyl group of PDMS (Akar et al., 2007).

In this work, block copolymers of polypyrrole (PPy) and thienyl end capped cyclohexanone formaldehyde resin (Th-CFR) were synthesized via chemical oxidative polymerization of (Py) and ThCFR in the presence of cerium (IV) oxodic dibenzoate (CODB). The treatment of Py with CODB was maintained in non-aqueous media at room temperature. Several solvents including toluene, dichloromethane, were used. Besides the role of reaction media, the effect of ceric (IV) oxodic compound on polymerization was investigated.

## 2. Experimental

### Materials

Pyrrole (Sigma-Aldrich), cerium (IV) ammonium nitrate (Alfa Aesar), benzoic acid (Merck), sodium hydroxide (Sigma-Aldrich), dichloromethane (Merck), toluene (J.T. Baker) and acetone were all reagent-grade chemicals of highest purity and were used without further purification. All solutions were prepared freshly before each experiment.

### Analyses

Infrared (IR) spectra were recorded on a Jasco FTIR 5300 Fourier transform infrared spectrometer.

Electrical conductivities of polymers were determined by four point probe technique using Keithley 2400 model multimeter, Lucas Labs 302 model probe holder and SP4-180-TFS type probe. Thin pellets with typical sample diameter of 13 mm were prepared by compaction of the polymer powders under 10 tons of pressure.

$$\sigma = V^{-1} \cdot I \cdot (\ln 2 / \pi d_n) \quad (1)$$

where V is the potential (Volt), I is current (Amper) and  $d_n$  is the thickness of the samples (cm).

The morphology of the products was examined by scanning electron microscopy (SEM; ESEM XL30 ESEM-FEG, Philips) and the samples for the SEM measurement were prepared by platinum coating.

### Synthesis of thiophene-2-carbonyl chloride and cyclohexanone formaldehyde resin

**Synthesis of CFR** - Into a three-necked flask equipped with a stirrer and a condenser, 104 ml of cyclohexanone, 25 ml of cyclohexane and 30 ml of 37 per cent formalin were added. When the temperature of the mixture was raised to 65-70 °C, refluxing started. Subsequently, 100 ml of 37 per cent formalin and 3.64 ml of 20 per cent NaOH were mixed and added continuously at gradually increasing rate sufficient enough to maintain vigorous refluxing. The reaction was further continued under pH values of 11-12 for 3 hours with 20 per cent NaOH aqueous solution. After reaction time was completed, two layers were formed. The cyclohexanone formaldehyde resin was separated and purified by decanting the water layer. CFR was washed several times with hot water until it was free from formaldehyde odour, and it was dried at 110 °C in vacuum for 5 hours (Kızılcın and Akar, 1996).

**Synthesis of the comonomer ThCFR** - In a flange flask fitted with a multiple socket cooled carrying a mechanical stirrer, a dropping funnel and a thermometer, 35 ml of chloroform, 10 g of CFR and 2 ml pyridine were placed. The flask was cooled on an ice bath, while stirring vigorously under nitrogen. Subsequently, the solution of 2.67 ml of ThCCl in 5 ml of chloroform was added to the resin solution dropwise under stirring. The pink-coloured solution was allowed to stand at 0 °C for 24 hours, then was diluted with 150 ml of chloroform and transferred to a separatory funnel. It was washed successively with several portions of diluted aqueous HCl (5 per cent of 100 ml) water-saturated aqueous sodium hydrogen carbonate and hot water. Eventually, the mixture was poured into 50 ml of hexane. Then the precipitate was dried at 25 °C in vacuum. The resin was modified with thiophene-2-carbonyl chloride using mol ratio of CFR to ThCCl as 1/2 to give ThCFR (Ates et al., 2015).

### Synthesis of Ce(IV) Oxidic Dibenzoate

Benzoic acid (9.76 g, 0.08 mol) was placed in a reaction vessel and pure water (80 ml) was added. Sodium hydroxide (3.2 g, 0.08 mol) was added slowly through a dropping funnel at room temperature. The mixture was stirred for 15 minutes, so a 0.57M sodium benzoate solution was produced. Ceric ammonium nitrate (10.96 g, 0.02 mol, 0.25 M) was dissolved in water (80 ml) and the solution was added to the sodium benzoate solution through a dropping funnel over a period of 15 minutes. A light yellowish thick material precipitated. The solution was filtered and washed with water, and finally dried at 45 °C for 24 hours (Hawkins & Mauermann, 1995).

### Preparation of Pyrrole - Thienyl End Capped Cyclohexanone Formaldehyde Resin Copolymers

Resin was dissolved in solvent (10 ml). After stirring for 15 minutes, constant amount of pyrrole (0.3 ml) was added and the stirring process was continued. Oxidation solution was prepared with same solvent (40 ml) as used for polymer-solution. Synthesized cerium (IV) oxodic benzoate was added with different ratios to solvent and after 15 minutes of stirring compounded drop wise with polymer-solution. While mixing solutions a black powder formed almost instantaneously. The color of the solution changed within few minutes from first pale greenish to finally black. Experimental work was carried out at room temperature and stirring process was maintained with a magnetic stirrer. After polymerization, the powder was filtered by means of filter paper and funnel, washed with solvent and acetone several times, and dried at 45 °C.

### 3. Results and Discussion

In this study, copolymers of polypyrrole and thienyl end capped cyclohexanone formaldehyde resin (ThCFR-b-PPy) were synthesized with a novel cerium (IV) based oxidant (CODB). Copolymerization reaction is demonstrated in Figure 1.




Fig. 1. Synthesis of ThCFR-b-PPy.

Reaction conditions were summarized in Table 1. The influence of solvent type, CODB to Py mol ratio and reaction time on the yield and conductivities of the copolymers were investigated. As the results were compared in terms of yield of the copolymer it was found that increasing the mol ratio of CODB to Py or reaction time increased

the yield of product. The effect of the solvent type was found to be negligible. Conductivities of copolymers were measured in the range of  $10^{-7}$ - $10^{-6}$  S/cm. It was suggested that the long treatment of pyrrole with the oxidant resulted in copolymers with low electrical conductivities.

Table 1. Summary of the experimental work.

#	Solvent	Resin	$n_{\text{CODB}}/n_{\text{Py}}$	$n_{\text{py}}/n_{\text{resin}}$	Time (h)	Yield (%)
1	Dichloromethane	-	0.5	-	24	26
2	Dichloromethane	ThCFR	0.5	100	1	3
3	Toluene	ThCFR	0.5	100	1	2
4	Dichloromethane	ThCFR	0.5	100	2	3
5	Dichloromethane	ThCFR	0.5	100	24	26
6	Dichloromethane	ThCFR	1.0	100	24	53
7	Dichloromethane	ThCFR	0.5	50	24	22
8	Dichloromethane	ThCFR	0.33	100	24	9
9	Dichloromethane	CFR	0.5	100	24	22

The structures of comonomer ThCFR and copolymer ThCFR-b-PPy were confirmed by spectroscopic investigations. Infrared spectrum of the modified resin is outlined in Figure 2. Absorption bands at  $3450\text{ cm}^{-1}$  including stretching vibrations of  $\text{-OH}$  groups. The FTIR spectrum of ThCFR indicated signal corresponding to aromatic groups of the thiophene and gave the characteristic ester band at  $1712\text{ cm}^{-1}$ . Aromatic ring vibration of thiophene  $\text{-C=C-}$  appears as a peak at about  $3050\text{ cm}^{-1}$ ,  $1600\text{ cm}^{-1}$  and out of plane stretching vibrations of  $\text{=C-H}$  has a peak at  $750\text{ cm}^{-1}$ . Figure 3 represents the spectrum of ThCFR-b-PPy. The strong absorption bands at  $1400$  and  $1500\text{ cm}^{-1}$  belong to pyrrole ring and support formation of the copolymer.




Fig. 2. FTIR spectrum of the comonomer, ThCFR.




Fig. 3. FTIR spectra of the copolymer, ThCFR-b-PPy.

The surface properties of ThCFR-b-PPy copolymer (Sample #7) is demonstrated in Figure 4. Morphology of the copolymer consists of smooth blocks and spherical particles that are attributed to resin and polypyrrole, respectively.




Fig. 4. SEM micrographs of ThCFR-b-PPy, copolymer.

This study has brought a new approach to synthesis of copolymers of polypyrrole suggesting the use of a novel Ce (IV) based oxidant. The organic origin of the oxidant enables performing the copolymerization reactions in solvents such as dichloromethane and toluene, the solvents favorable for solubility of various insulating polymers.

## References

- De Leon A., Advincula C.R. (2015). Conducting Polymers with Superhydrophobic Effects as Anticorrosion Coating. Department of Macromolecular Science and Engineering, Case Western Reserve University, 2100 Adelbert Rd., Cleveland, OH, USA
- Chiang, C., Fincher, C., Park, Y., et al. (1977). Electrical conductivity in doped polyacetylene, *Phys. Rev. Lett.*, 39:1098.
- Dall'Olio, A., Dascola, G., Varacca, V., et al. (1968). Electron paramagnetic resonance and conductivity of an electrolytic oxypyrrole [(pyrrole polymer)] black C R Acad Sci Ser. IIc: Chim., C267:433.
- Diaz, A. F., Kanazawa, K. K., Gardini, G. P., (1979). Electrochemically prepared polypyrroles from aqueous solutions. *J. Chem. Soc. Chem. Commun.*, 635.
- Kızılcın, N., Ustamehmetoglu, B., Öz, N., Sarac, A. S., Akar, A., (2001). Soluble and conductive polypyrrole copolymers containing silicone tegomers. Department of Chemistry, Faculty of Science, Istanbul Technical University, 34469 Maslak, Istanbul, Turkey.
- Gardini, G. P. (1973). In *Advances in Heterocyclic Chemistry*; Katritzky, A. R.; Boulton, A. J., Eds.; Academic: New York; p 67.
- Sarac, A. S., Erbil, C., Ustamehmetoglu, B., (1994). *Polym. Bull.*, 33, 535.
- Hafaid, I., Chebil, S., Korri-Yousoufi, H., Bessueille, F., Errachid, A., Sassi, Z., Ali, Z., Abdelghani, A., Jaffrezic-Renault, N., (2010). Effect of electrical conditions on an impedimetric immunosensor based on a modified conducting polypyrrole, *Sens. Actuat. B: Chem.*, 144, 323.
- Chartuprayoon, N., Hangarter, C. M., Rheem, Y., Jung, H., Myung, N. V., (2010). Toward a chemiresistive ammonia (NH<sub>3</sub>) gas sensor based on viral-templated gold nanoparticles embedded in polypyrrole nanowires *J. Phys. Chem. C* 114.
- Cho, K. Y., Lim, H. G., Yun, S. R., Kim, J., Kang, K. S., (2008). Electric field frequency and strength effects on Au-electrode damage for an electroactive paper actuator coated with polypyrrole. *J. Phys. Chem.*, C 112, 7001.
- Guo, Y. B., Zhang, Y. J., Liu, H. B., Lai, S.-W., Li, Y. L., Li, Y. J., Hu, W. P., Wang, S., Che, C.-M., Zhu, D. B., (2010). Assembled organic/inorganic p-n junction interface and photovoltaic cell on a single nanowire. *J. Phys. Chem. Lett.* 1, 327.
- Wu, J. H., Li, Q. H., Fan, L. Q., Lan, Z., Li, P. J., Lin, J. M., Hao, S. C., (2008). Solar Energy Conversion: Chemical Aspects. *J. Power Sources*, 181, 172.
- Joo, J., Lee, C. Y., (2000). High frequency electromagnetic interference shielding response of mixtures and multilayer films based on conducting polymers. *J. Appl. Phys.*, 88, 513.
- Schaffinghen, T. V., Joiret, S., Deslouis, C., Terryn, H., (2007). *J. Phys. Chem.*, C 111.
- Guimard, N. K., Gomez, N., Schmidt, C. E., (2007). Conducting polymers in biomedical engineering. *Prog. Polym. Sci.* 32, 876.
- Ge, J., Neofytou, E., Cahill 3rd, T. J., Beygui, R. E., Zare, R. N., (2012). Drug release from electric-field-responsive nanoparticles. *ACS Nano*, 6, 227.
- Liao, Y., Wang, X., Qian, W., Li, Li, Y. X., Yu, D.-G. (2012). Bulk synthesis, optimization, and characterization of highly dispersible polypyrrole nanoparticles toward protein separation using nanocomposite membranes, *Journal of Colloid and Interface Science.*
- Öztürk T. and Cakmak. I., (2007). Synthesis of block copolymers via redox polymerization process: A critical review. Department of Chemistry, Kafkas University, 36200, Kars, Turkey.



- Nagarajan, S., Srinivasan, K. S. V., (1994). Redox polymerization process: An efficient tool for the synthesis of block copolymers. *Eur. Polym. J.*, 30, 113-119.
- Nagarajan, S., Srinivasan, K. S. V., (1995). Redox polymerization process: An efficient tool for the synthesis of block copolymers, *J. Polym. Sci. Pol. Chem.*, 33, 2925-2933.
- Wodka, T. J., (1993). Studies on the synthesis of block copolymers of acrylonitrile and ethylene oxide. *Appl. Polym. Sci.*, 47, 407-416.
- Nagarajan, S., Sudhakar, S., Srinivasan, K. S. V., (1994). Block copolymerization initiated by Mn(III)-poly(ethylene glycol) redox system-general features and kinetics. *Colloid Polym. Sci.*, 272, 777-783.
- Cakmak I., (1993). Preparation of multiphase block copolymers by redox polymerization process. 2: Polymerization of acrylonitrile by the manganese(III)-poly(ethylene glycol) redox system. *Die Angew. Macromol. Chem.*, 211, 53-60.
- Trahanovsky, W. S., Young, L. B., Brown, G. L., (1967). Oxidation of organic compounds with cerium(IV). 4: Oxidation of benzyl and related alcohols. *J. Org. Chem.*, 32, 3865.
- Leza, M. L., Guzman, G. M., (1999). Ceric salt initiated polymerization of 4-vinylpyridine. *Eur. Polym. J.*, 27, 445-447.
- Saldick, J., (1956). Thermal initiation of vinyl polymerization by ceric solutions. *J. Polym. Sci.*, 19, 73-75.
- Venkatakrishnan, S., Santappa, M., (1958). Thermal polymerization of methyl acrylate initiated by ceric ion in aqueous solution. *Makromol. Chem.*, 27, 51-60.
- Ananthanarayanan, V. S., Santappa, M., (1965). Kinetics of vinyl polymerization initiated by ceric ion in aqueous solution. *J. Polym. Sci.*, 9, 2437-2448.
- Mino, G., Kaizerman S., (1958). A new method for the preparation of graft copolymers: Polymerization initiated by ceric ion redox systems. *J. Polym. Sci.*, 31, 242-243.
- Misra, G. S., Arya B. D., (1984). Aqueous polymerization of methacrylic-acid initiated by Ce+4-glycolic acid redox pair, *J. Polym. Sci.*, 22, 3563-3569.
- Fernandez, M. D., Guzman G. M., (1989). Aqueous polymerization of methyl-methacrylate initiated by Ce+4- alcohol redox system-effect of acid concentration and additives. *J. Polym. Sci. Pol. Chem.*, 27, 2427-2433.
- Sudhakar, D., Srinivasan, K. S. V., Joseph, K. T., Santappa, M., (1979). Grafting of methyl-methacrylate to nitrocellulose by ceric ions. *J. Appl. Polym. Sci.*, 23, 2923-2928.
- Singh, B. C., Misra, B. K., Rout A., Mallick N., Rout M. K., (1979). Kinetics of inhibited or retarded polymerization-investigation on the cerium(IV)-toluene-acrylonitrile system. *Makromol. Chem.*, 180, 953-1968.
- Mino, G., Koizerman, S., Rasmussen, B., (1959). The polymerization of acrylamide initiated by ceric nitrate-3-chloro-1-propanol redox systems. *J. Polym. Sci.*, 38, 393-401.
- Mohanty, M., Pradkan, B., Mohanta, M. C., (1979). Vinyl polymerization of acrylonitrile by the cerium(IV)-propane-1,2-diol system. *Eur. Polym. J.*, 15, 743-746.
- Subramanian, S. V., Santappa, M., (1968). Ceric ion-reducing agent redox initiated vinyl polymerization. *Makromol. Chem.*, 112, 1.
- Subramanian, S. V., Santappa, M., (1968). Vinyl polymerization initiated by ceric ion reducing agent systems in sulfuric acid medium. *J. Polym. Sci.*, 6, 493.
- Saha, S. K., Chaudhuri, A. K., (1972). Effect of amines on ceric ion-initiated polymerization of vinyl monomers. 2: Polymerization of acrylonitrile by ceric ion in presence of various substituted amines. *J. Polym. Sci.*, 10, 797-799.
- Chakrabarty, N. K., Chaudhuri, A. K., (1985). Polymerization of acrylonitrile with ceric ion-2-propanethiol as initiator system. *J. Macromol. Sci. Chem.*, A22, 1961-1709.
- Pramanick, D., Chatterjee, A. K., Sarkar, S. K., (1979). Ceric salt thiourea redox initiator system for vinyl polymerization. *Makromol. Chem.*, 180, 1085-1088.
- Kızılcan, N. and Akar, A. (1996). Modification of acetophenone - formaldehyde and cyclohexanone formaldehyde resins, *Journal Of Applied Polymer Science*, Vol. 60 No. 3, pp. 465-476.
- Uyanık, N., Yıldırım, H., Kızılcan, N. and Akar, A. (1991). Preparation of block and graft copolymers by peroxy carbamates. *Angew. Macromol. Chem.*, Vol. 191, pp. 1-13.
- Uyanık, N., Kızılcan, N. and Akar, A. (1998). ABA Type block copolymers containing poly(dimethylsiloxane) and ketonic resin. *J. Appl. Polym. Sci.*, Vol. 67 No.1, pp. 643- 8.
- Uyanık, N., Yalçinkaya, H., Kızılcan, N. (2001). Poly(dimethyl siloxane)-containing five-block copolymers: Effects of resin blocks. *Surface Coat. Inter. Part B: Coating Transactions*, Vol. 84, No. 4, pp. 309-16.
- Kızılcan, N. and Koşar, Ö. (2012). Carbazole modified ketonic resins. *Pig. & Resin Tech.*, Vol. 41 No. 2, pp. 81-90.
- Kızılcan, N. (1999). Ketonic resins as free radical photoinitiators. *J. Appl. Polym. Sci.*, Vol. 72 No. 7, pp. 927-34.
- Ustamehmetoğlu, B., Sarac, S., Kızılcan, N. and Akar, A. (2004). Electroinduced oxidative copolymerisation of N-vinyl carbazole with methyl ethyl ketone formaldehyde resin. *Polym. Advan. Technol.* Vol., 15 No. 1, pp. 365- 9.
- Ustamehmetoğlu, B., Yazıcı, P. and Kızılcan, N. (2011). Polymerization of carbazole-9-carbonyl chloride modified methyl ethyl ketone formaldehyde resin. *Pig. & Resin Tech.*, Vol. 40 No.4 , pp. 211-21.
- Ustamehmetoğlu, B., Kızılcan, N., Kelleboz, E., and Akar, A. (2012). Copolymer of carbazoles and methyl ethyl ketone formaldehyde resin. *Pig. & Resin Tech.*, Vol. 41 No.1 , pp. 25 – 33.
- Kızılcan, N., Ustamehmetoğlu, B. (2005). Chemical polymerisation of pyrrole in the presence of ketone-formaldehyde resins. *Appl. Polym. Sci.*, Vol. 96 No. 1, pp. 618- 24.
- Kızılcan, N., Hocaoglu, B., Ustamehmetoğlu, B. (2011). Polymerisation of carbazole-9-carbonyl chloride modified cyclohexanone formaldehyde resin. *Pig. & Resin Techn.*, Vol. 40 No. 3, pp. 143- 53.
- Ergun, S., Kızılcan, N. and Onen, A. (2007). Block copolymers of cyclohexene oxide and ketonic resins via condensation and promoted cationic polymerisation. *J. Appl. Polym. Sci.*, Vol. 105 No. 3, pp. 1012- 7.
- Çanak, T. Ç., Kızılcan, N. and Serhatlı, İ. E. (2011). Synthesis of acetophenone formaldehyde resin containing ABA type block copolymers by ATRP. *J. Appl. Polym. Sci.*, Vol. 119 No.1, pp. 183 - 9.
- Çanak, T. Ç., Kızılcan, N. and Serhatlı, İ. E. (2012). Synthesis of cyclohexanone formaldehyde resin-methylmethacrylate block-graft copolymers via ATRP. *J. Appl. Polym. Sci.*, Vol. 123 No.5, pp. 2628- 35.

- Akar, A., Kizilcan N., Ustamehmetoglu, B., Colak, D., Sarac A. S. and Colak C. (2007). Block copolymers of N-vinyl carbazole and  $\alpha,\omega$ -dihydroxy polydimethylsiloxane. *J. Appl. Polym. Sci.*, Vol. 106 No. 6, pp. 3694– 702.
- Ates, E., Kizilcan, N. and Istif, M. (2015). New comonomer synthesis from thiophene-2-carbonyl chloride and cyclohexanone formaldehyde resin. *Pigment & Resin Technology*, Vol. 44 No.2, pp.79-86
- Hawkins, I. M. & Mauermann, H .H. K. (1995). Cerium (IV) catalyst compounds and promoting combustion of hydrocarbon fuels therewith. *US Patent* 5 449 387.